2004 - 2009 Cadillac XLR: Service Bulletin: #PIC3998B: Flash To Pass Inoperative With Headlamps Off

#PIC3998B: Flash To Pass Inoperative With Headlamps Off - keywords beam dimmer discharge head headlight HID high highbeam intensity lamp light low switch - (Nov 11, 2008)

Subject: Flash To Pass

Inoperative With Headlamps Off

Models: 2004 - 2009 Cadillac

XLR

2006 - 2009 Cadillac

DTS

This PI was superseded to update model years. Please discard PIC3998A.

The following diagnosis might be helpful if the vehicle exhibits the symptom(s) described in this PI.

Condition/Concern:

The Cadillac XLR and DTS use a single High Intensity Discharge (HID) lamp on each side of the vehicle. These lamps perform both high and low beam headlamp functions through the use of a plate built into the lamp. This plate partially covers the lamp during low beam operation and fully retracts during high beam operation.

When first turned on, HID Headlamps may take a few seconds to reach full intensity. As a result, the flash to pass feature does not operate unless the headlamps are already illuminated.

Recommendation/Instructions:

This is a normal characteristic. No repair attempts should be made.

Please follow this diagnostic or repair process thoroughly and complete each step. If the condition exhibited is resolved without completing every step, the remaining steps do not need to be performed.

Online URL:

https://www.xlr-net.com/knowledgebase/article/2004-2009-cadillac-xlr-service-bulletin-pic3998b-flash-to-pass-inoperative-with-headlamps-off-158.html