



## 2006 Cadillac XLR-V: Service Information: Cross Drilled Rotors

Cross-drilled brake rotors (fig. 16 -attached) are being used on the 2005 1/2 Pontiac Grand Prix GXP, and available on the 2005 Chevrolet C6 Corvette and the upcoming Cadillac XLR-V.



If required, these brake rotors can be machined on a lathe in a similar manner to standard rotors.

***TIP:*** When cutting rotors, use positive rake tooling on the lathe (fig. 17 -attached). Positive rake tooling requires less cutting pressure, reduces chatter, and improves surface finish. When setting up the brake lathe, be sure to use a vibration dampener/silencer.



Using SI procedures, apply a non-directional finish to the rotor surface after machining by using a sanding block and 150-grit aluminum oxide sandpaper.

*- Thanks to Fred Tebbets and Rob Coultres, GM Techlink, May 2005*

General Motors bulletins are intended for use by professional technicians, not a "do-it-yourselfer". They are written to inform those technicians of conditions that may occur on some vehicles, or to provide information that could assist in the proper service of a vehicle. Properly trained technicians have the equipment, tools, safety instructions and know-how to do a job properly and safely. If a condition is described, do not assume that the bulletin applies to your vehicle, or that your vehicle will have that condition. See a General Motors dealer servicing your brand of General Motors vehicle for information on whether your vehicle may benefit from the information.

**© Copyright General Motors Corporation. All Rights Reserved**

Online URL:

<https://www.xlr-net.com/knowledgebase/article/2006-cadillac-xlr-v-service-information-cross-drilled-rotors-66.html>